


Where Digital Innovation Meets Intuitive Functionality





Google EDLA



Easy Connection & Sharing



User Friendly Experience



Security & Compatibility



Remote-control Services

TR3DK					
	Size	248.92 cm (98), 218.44 cm (86), 190.5 cm (75), 165.1 cm (65), 139.7 cm (55)			
Display	Native Resolution	3,840 × 2,160 (UHD)			
	Brightness	440 nits (Max.)			
Touch	Multi-Touch Point	Max. 40 Points			
Software	OS Ver.	Android 13 (EDLA)			
Connectivity	Input	HDMI (3, HDCP2.2), RGB (1, VGA), Audio (1), RS-232C (1), RJ45 (1, LAN), USB3.0 Type A (4), USB2.0 Type A (1), USB Type-C (1, USB-PD, DP-Alt)			
	Output	HDMI (1), Audio Out (1, Optical 1(SPDIF)), Touch USB (2), RJ45 (1, LAN)			


CREATIVE WHITEBOARD SOLUTION



Multi-touch

LG CreateBoard can simultaneously detect up to 40 points for multi-touch functionality. With a lifelike board touch experience, it allows people to write and touch at the same time, making it easy to collaborate and share ideas with teammates. This boosts efficient interaction in group activities or meetings.

- * A max of 32 points are recognized in the Android environment, and a max of 40 points are detected in the Windows environment.
- * Up to 10 points can be recognized in the writing app.




Easy to Save / Import / Export

LG CreateBoard includes simple import and export functionality. Resources can be saved and imported directly to and from Google Drive or OneDrive, and files can be imported from a USB drive (Users can browse resources saved on USB storage). After the meeting, users can easily save and export content through a simple touch. Additionally, users can directly send it via email to share with others or transfer the data to a personal device by scanning a QR code.


LG CREATEBOARD LAB

LG's proprietary whiteboarding software



Tools for Fluid Collaboration

A variety of tools such as a calculator, clock, and sticky note are available to facilitate smooth discussions and ensure seamless idea sharing and communication. Also, users can personalize the menu bar with their most frequently used tools, thereby improving their work efficiency.



Web Browser


When you need a reference during a discussion, you can access various information in real time with the simple click of a web browser. The necessary information found on the internet can be easily dragged and dropped into the material you're creating, enhancing the productivity of your meetings.



Attention Effect

By simply double-tapping the LG CreateBoard screen with 4-5 fingers, an attention sign will pop up with a sound. This feature makes it easy to capture the participants' attention during moments when you need them to focus.

EASY CONNECTION & SHARING



Wireless ScreenShare

LG CreateBoard Share enables users to show up to 9 shared screens or a file on a screen in real-time when the LG CreateBoard Share app is installed on the device. Presenters can flip through PPTs remotely and conveniently send photos/videos stored on their device for smoother presentations.

- * LG CreateBoard also supports app-less sharing for PC (via website) and mobile devices within the same network.
- * For a more stable connection, we recommend the installation of a dedicated app (LG CreateBoard Share).



Bluetooth Connectivity

LG CreateBoard supports wireless Bluetooth connections to various devices such as a speaker, mouse, keyboard, etc. This is optimal for building a hybrid environment so that online and offline meetings can proceed smoothly.



C-type Connection

USB-C connectivity simplifies connections which enables charging and sending data simultaneously over just one single cable.

* USB Type-C cables are sold separately.

REMOTE MANAGEMENT SOLUTION



LG ConnectedCare DMS

LG ConnectedCare DMS is a cloud solution for remotely monitoring, controlling, and managing the status of LG CreateBoard installed in educational environments. This feature enables IT managers to operate and manage important resources on operating devices without physically visiting sites.

- * 'LG ConnectedCare DMS' needs to be purchased separately.
- * The availability of the 'LG ConnectedCare DMS' service differs by region, so please contact the LG sales representative in your region for more details.
- * LG ConnectedCare DMS supports the TR3 Series as of now(plus more to come) under a cloud environment.




Remote-control / Scheduling

Messages and a range of other content can be sent from the main



Broadcasting / Alert Messaging

Messages and a range of other content can be sent from the main system to individual devices connected to LG Connected-Care DMS. In case of urgent occasions such as a fire or a natural disaster, alert messages can be distributed manually across the system, which help people promptly take safety action.



Threshold Settings

Users can set thresholds in eight categories including display temperature, memory usage, or signal, and can receive warning or error notifications based on their threshold settings.

Monitoring & Fault Diagnosis

An engineer can check the status in real-time and diagnose problems remotely. Also, the current status of issues can be categorized, allowing for easy viewing and quick responses.

Issue Management

Remote issue management can be carried out by the LG ConnectedCare DMS solution. This makes management safer and more efficient, facilitating the stable operation of the devices.

GOOGLE CERTIFICATION



Google Certification

LG CreateBoard has received Google certification, enabling users to seamlessly integrate with the Google ecosystem by connecting their Google accounts.

* Exceptions apply in countries without Google services.



Google Play Store

Users have access to the Google Play Store, where they can download a wide range of applications, including education-related games, tools, and more for an expanded experience.

* Exceptions apply in countries without Google services.

SECURITY FUNCTION



Screen Lock

Uers can lock the screen using the Screen Lock function, and unlock it by entering a password. Users can set the Screen Lock in the Settings menu to protect the device from unidentified users.



USB Lock Mode

USB Lock Mode is a security measure that helps prevent data from being copied to unauthorized devices, which is essential when being used in spaces where security is critical.



Secure Mode


LG CreateBoard supports Secure Mode that disables the LG CreateBoard Share function to prevent unauthorized content from being shown on various devices.



Auto-remove Files

Users can set LG CreateBoard to delete files regularly for enhanced security.

OTHER FEATURES



QR Login for Easy Cloud Access

The QR code on the home screen reduces preparation time for meetings by enabling personal device verification. Users can sign up for a variety of apps on the LG CreateBoard including Google Drive and OneDrive with just one QR verification without any additional login process. Once a lesson is finished, users can simply click the Logout button to disconnect, thus the risk of a personal information leak is reduced.



Front Connectivity Design


LG CreateBoard features front display ports and speakers enabling content to be delivered easier with more immersive sound.



Smart Viewing


With Smart Viewing function, two or more materials can be displayed on the same screen simultaneously without having to repeat Alt-tab.

- * Multi window mode may not work for some apps.
- * PIP mode is available for the external source screen.



Advanced Eye-Care

LG CreateBoard has introduced a flicker-free function. With the reduced flickering of the monitor's backlight, users can use the device with more comfort even when using it for a long time.



Built-in OPS Slot


LG CreateBoard supports OPS slots, allowing you to easily and conveniently mount OPS desktop at the back of the LG CreateBoard without the hassle of connecting to an external desktop, offering you more expanded functions.

* OPS : Open Pluggable Specification



Power Saving

When a device doesn't receive an external input signal for a specific amount of time set by the user, the device goes into standby mode. Devices can also be automatically turned on or off at specific time or day set by the user, which contributes to save energy.



SPECIFICATION

		Model Name		98TR3DK-I	86TR3DK-I	75TR3DK-I	65TR3DK-I	55TR3DK-I		
		Screen Size		248.92 cm (98)	218.44 cm (86)	190.5 cm (75)	165.1 cm (65)	139.7 cm (55)		
		Panel Technology				IPS				
		Back Light Type		Direct						
		Aspect Ratio		16:9						
		Native Resolution		3840 x 2160 (UHD)						
Panel		Refresh Rate		60 Hz						
		Brightness		440 nits						
		Contrast Ratio		1,550 5007	1,000,000	1200:1				
		Color gamut		NTSC 72%	NTSC 68%	1=00 (11 (1)	NTSC 72%			
		Viewing Angle (H x V)				178° (H/V)				
		Color Depth		1.07B (10bit)						
		Response Time Surface Treatment (Haze)		8ms Haze 25% Haze 28% Haze 25%						
				Haze 25%	Haze 28%	16 / 7	Haze 25%			
	1	Operation Hours (Hours/Day) Digital HDMI		16 / 7 HDM (3) HDCP2 2						
		Analog	RGB	HDMI (3) HDCP2.2 Yes (1, VGA)						
		Audio In Yes (1)								
	Input	RS232C IN				Yes (1)				
		RJ45 (LAN)				Yes (1)				
Connectivity Jack Interface)		USB		Yes (1) USB3.0 Type A (4), USB2.0 Type A (1), USB Type-C (1, USB-PD, DP-Alt)						
		Display Out			0380.0 Type 71 (1), 0.	HDMI Out (1)	c (1, 035 1 5, 51 7 (c)			
		Audio Out				(1, Optical 1 (SPDIF)				
	Output	Touch USB 2.0				Yes (2)				
		RJ45(LAN)		Yes (1)						
		Bezel Color				Black				
				T/R/L/B:	T/R/L/B:	T/R/L/B:	T/R/L/B:	T/R/L/B:		
		Bezel Width		30/27/27/45 mm	15/15/15/44 mm	15/15/15/44 mm	15/15/15/44 mm	18/18/18/45 mm		
		Weight (Head)		103.6 Kg	58.6 Kg	47.3 Kg	35.0 Kg	26.1 Kg		
Mechanio Specificat		Packed Weight		126.5 Kg	75.9 Kg	60.6 Kg	44.7 Kg	34.5 Kg		
Specificat	1011	Monitor Dimension (W x	H x D)	2244 × 1323 × 91 mm	1957 × 1160 × 100 mm	1709 × 1020 × 88 mm	1488.4 × 896.6 × 87.2 mm	1271 × 774 × 87 mm		
		Carton Dimensions (W x	H x D) (Box outer size)	2406 × 280 × 1474 mm	2110 × 1283 × 225 mm	1863 × 1140 × 225 mm	1628 × 1005 × 208 mm	1401 × 859 x 220 m		
		Handle				Yes				
		VESA™ Standard Mount	Interface		800 × 600 mm		600 × 400 mm	400 × 200 mm		
		Wi-Fi	Built-in			Slot type				
	HW	Sensor	Auto Brightness sensor			Yes				
		Power Indicator Yes								
		Operating System				Android (13 EDLA)				
Key Feature		Background Image	Booting Logo Image	Yes						
	SW	Multi-screen	PIP	Yes (1 external source)						
		Widter Screen	PBP	Yes (1 external source)						
		Screen Share	1	LG CreateBoard Share						
		Power	Smart Energy Saving			Energy Saving				
			Wake on LAN			Yes				
						0 ~ 40 °C				
Environment Co	onditions	Operation Temperature			10 ~ 90 % RH					
Environment Co	onditions	Operation Humidity								
Environment Co	onditions	Operation Humidity Power Supply				100-240V~ 50/60 Hz				
	onditions	Operation Humidity Power Supply Power Type		450 W	205.W	100-240V~ 50/60 Hz Built-In Power	220 W	470.14		
	onditions	Operation Humidity Power Supply Power Type Typ.		460 W	385 W	100-240V~ 50/60 Hz Built-In Power 225 W	220 W	170 W		
	onditions	Operation Humidity Power Supply Power Type		630 W	580 W	100-240V~ 50/60 Hz Built-In Power 225 W 430 W	420 W	395 W		
		Operation Humidity Power Supply Power Type Typ.	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V~ 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.),	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power		Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni	t)	630 W	580 W	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max)	420 W	395 W		
Power		Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) ≤0.5 W	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Power Consul	mption	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V-50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) ≤0.5 W ≤0.5 W	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power	mption	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Power Consul	mption	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) <0.5 W 50.5 W 50.5 W CB / NRTL	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Consul Sound Certificat	mption	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) ≤0.5 W ≤0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Consul	mption	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Consul Sound Certificat OPS Compat	mption ion	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V-50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.),		
Power Consul Sound Certificat	mption ion	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare	t)	630 W 1348 BTU/Hr(Typ.),	580 W 1314 BTU/Hr(Typ.),	100-240V-50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes	420 W 751 BTU/Hr(Typ.),	395 W 580 BTU/Hr(Typ.)		
Power Consul Sound Certificat OPS Compat	mption don dibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in	t)	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max)	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) <0.5 W <0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes DMS (Paid License)	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max)	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS	t)	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, K Romania	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W \$15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, Pin, Spanish, Swedish, Hungai	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compati	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic	t)	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, K Romania	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) 50.5 W 50.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, Pun, Spanish, Swedish, Hungan Type A-Type B) 5 M*1, HDMI mote Controller(include bat	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compati	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time	t)	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, K Romania	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, P in, Spanish, Swedish, Hungal in, Spanish Controller (include bat	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy	t)	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, K Romania	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) <0.5 W 50.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, Pin, Spanish, Swedish, Hungai Type A-Type B) 5 M*1, HDM mote Controller (include bat 55 ms ±1 mm	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compati	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy Interface		630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) (orean, Norwegian, Polski, P n, Spanish, Swedish, Hungai Fype A-Type B) 5 M*1, HDM mote Controller (include bat \$5 ms ±1 mm USB 2.0	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) prtugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy Interface Protection Glass Thickne	ss	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, P In, Spanish, Swedish, Hungai Sype A-Type B) 5 M*1, HDM mote Controller (include bat \$5 ms \$1 mm USB 2.0 d glass with 9H level 7 Moh	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare LG ConnectedCare Type Compatible OSD Basic Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo	ss	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, P In, Spanish, Swedish, Hungai Type A-Type B) 5 M*1, HDM mote Controller/iculde bat \$5 ms ±1 mm USB 2.0 d glass with 9H level 7 Moh /Mac/Android (Linux/Mac S	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point	ss	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W \$15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, Pan, Spanish, Swedish, Hungan Type A-Type B) 5 M*1, HDM mote Controller(include bat \$5 ms £1 mm USB 2.0 d glass with 9H level 7 Moh Mac/Android (Linux/Mac S Max 40 points	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare LG ConnectedCare IG ConnectedCare IG ConnectedCare IG ConnectedCare Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point SoC	ss	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V-50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, P (n; Spanish, Swedish, Hungal Type A-Type B) S M*1, HDM mote Controller(include bat \$5 ms ±1 mm USB 2.0 d glass with 9H level 7 Moh (Mac/Android (Linux/Mac S Max 40 points Quad core A55	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion ibility patibility	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point	SS rt	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) <0.5 W 50.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Xorean, Norwegian, Polski, Pin, Spanish, Swedish, Hungal Eype A-Type B) 5 M*1, HDM mote Controller (include bat 55 ms ±1 mm USB 2.0 d glass with 9H level 7 Moh /Mac/Android (Linux/Mac S Max 40 points Quad core A55 Mali G52MP2	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Languag Accesso Touch	mption ion bility e	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare LG ConnectedCare IG ConnectedCare IG ConnectedCare IG ConnectedCare Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point SoC	ss rt Storage	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Xorean, Norwegian, Polski, P III, Spanish, Swedish, Hungar Kype A-Type B) 5 M*1, HDM mote Controller (include bat \$5 ms \$1 mm USB 2.0 d glass with 9H level 7 Moh /Mac/Android (Linux/Mac S Max 40 points Quad core A55 Mali G52MP2 64 GB	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portuguesian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.) 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Software Comp Languag Accesso	mption ion bility e	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare LG ConnectedCare UG ConnectedCare UG ConnectedCare Sob Basic Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point Soc GPU Internal Memory	SS rt	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re Toughener Windows 7/8/10/Linux/	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Korean, Norwegian, Polski, Pin, Spanish, Swedish, Hungai fype A-Type B) 5 M*1, HDM mote Controller (include bat \$5 ms \$1 mm USB 2.0 d glass with 9H level 7 Moh (Mac/Android (Linux/Mac S Max 40 points Quad core A55 Mall G52MP2 64 GB 8 GB	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.), 1348 BTU/Hr(Max		
Power Consul Sound Certificat OPS Compat Languag Accesso Touch	mption ion bility e	Operation Humidity Power Supply Power Type Typ. Max. BTU (British Thermal Uni DPM Power off Speaker Safety EMC OPS type compatible OPS Power built in LG ConnectedCare LG ConnectedCare DMS OSD Basic Reponse Time Accuracy Interface Protection Glass Thickne Operating System Suppo Multi touch point SoC GPU	ss rt Storage	630 W 1348 BTU/Hr(Typ.), 2081 BTU/Hr(Max) English, I	580 W 1314 BTU/Hr(Typ.), 1979 BTU/Hr(Max) Denmark, Finnish, German, k Romania er Cord 3 M*1, USB Cable (1 User Manual, QSG, Re Toughener Windows 7/8/10/Linux/	100-240V- 50/60 Hz Built-In Power 225 W 430 W 768 BTU/Hr(Typ.), 1467 BTU/Hr(Max) \$0.5 W \$0.5 W \$0.5 W 15 W x 2 CB / NRTL FCC Class "A" / CE / KC Slot type Yes Yes DMS (Paid License) Xorean, Norwegian, Polski, P III, Spanish, Swedish, Hungar Kype A-Type B) 5 M*1, HDM mote Controller (include bat \$5 ms \$1 mm USB 2.0 d glass with 9H level 7 Moh /Mac/Android (Linux/Mac S Max 40 points Quad core A55 Mali G52MP2 64 GB	420 W 751 BTU/Hr(Typ.), 1433 BTU/Hr(Max) ortugues(Europe), Portugue: ian, Thai Cable 3 M*1, Writing Pen*2 tery 2ea), Wifi module	395 W 580 BTU/Hr(Typ.), 1348 BTU/Hr(Max,		

Creative Visualization
*Product suffix codes may vary as per production batch.
*Product limages shown are for representative purpose only. Actual product may vary.
*As a continuing policy of product development at LG Electronics, the design and specifications are subject to change. They may vary from model to model. Colour/shades may vary due to printing restrictions. E&OE.

. .









To know more about LG, visit www.lg.com/in/business For B2B Solutions/Product enquiries, please write to b2b.solutions@lge.com For B2B Service, please write to b2bsupport.india@lge.com



CIN No. U32107DL1997PLC220109